



THE LIME CENTRE

The Lime Centre Ltd, Hazeley Road, Morestead, Winchester, Hampshire SO21 1LZ
Tel: 01962 713636 | info@thelimecentre.co.uk | www.thelimecentre.co.uk

Product Name: Tradirend

- A new build lime render with gentle texture and patina in a range of natural colours.
- Applied onto blockwork with one to two base coats and one finish coat.
- Lime Green Tradirend is a premixed render finish coat made with natural hydraulic lime, white cement and additives carefully designed to make a durable high-performance render.
- Designed for application over Forte base coat.
- Ideal for new build block work.

Sand Grading

SG 0-1mm

RG 0-2mm

Colour

Full range – see Render Colour Chart
(Sample colour biscuits available)

Packaging

25kg bags. Store in a cool dry place and use within 8 months.

Coverage

A 25kg bag will cover approx. 3m² at 5mm thick. This does not include any allowance for wastage.

Surface Preparation

Scratch existing basecoat of Forte with a 'nail' or 'devil' float once the basecoat has hardened but is still 'green'. Scratch in a tight spiral action making light grooves. Dampen surface with mist spray in sufficient quantity to reduce excessive suction.

Mixing/Water Addition

Add the whole bag of Tradirend into drum or forced action mixer carefully avoiding creating excessive dust. Add 3.5 - 4.5 litres of clean water per bag. Mix for at least 10 minutes using drum mixer or use a mechanical whisk for 3 minutes.

Application

Apply Tradirend once the Forte base coats have had sufficient time to cure. Usually 3 - 4 days.

Tradirend should be applied to a straight, flat, dampened surface in one or two passes up to a maximum of 5mm. Each pass or layer of Tradirend should be applied while the first pass is still damp but has had time to "pull in".

Avoid over working. Use only a light mist spray if applying water to the surface of the finishing coat.

Finish with a wooden float and leave open textured or dress with a sponge to close off and reveal the aggregate texture.

Temperatures: above 5^o and below 30^oC

Working time: 1-2 hours.

Curing

Prevent all coats from drying out too rapidly. Lightly spray each coat with water if it is hot or the product is drying out too quickly.

Protect from adverse conditions such as frost, rain and wind, ideally using a fully sheeted scaffold when outside.

Decoration

Tradirend is a coloured render and does not require decoration but can be decorated with mineral paint.

Allow approx. 24 days drying time before decorating with mineral paint.

When decorating use mineral paints. Contact The Lime Centre for further advice or information about the full range of mineral paints.



THE LIME CENTRE

The Lime Centre Ltd, Hazeley Road, Morestead, Winchester, Hampshire SO21 1LZ
Tel: 01962 713636 | info@thelimecentre.co.uk | www.thelimecentre.co.uk

Safety Data

Hazard Statements:

- Causes skin irritation.
- Causes serious eye damage.
- May cause respiratory irritation.

Precautionary Statements:

- Keep out of reach of children.
- Wear protective gloves/protective clothing/eye protection/ face protection.
- In case of contact with eyes, rinse carefully with clean water for several minutes. In relevant cases, take out contact lenses if possible. Seek professional assistance for a Doctor (Hospital).
- If in contact with skin wash abundantly with soap and water.
- Avoid breathing dust/spray.
- If inhaled remove person to fresh air and keep at rest in a position comfortable for breathing.
- Dispose of contents via conventional waste management facilities. Before disposal NHL lime should be made inert by wetting to induce hardening and bags should be completely emptied

Control Measures:

- Corrosive to brass and aluminium.
- Keep away from strong oxidising agents.
- Prevent alkaline run off from entering storm drains.



Lime Green Products Ltd

EN 998-1

**Prescribed General Purpose (GP) Render
and Plaster for internal and external
use**