



THE LIME CENTRE

The Lime Centre Ltd, Hazeley Road, Morestead, Winchester, Hampshire SO21 1LZ
Tel: 01962 713636 | info@thelimecentre.co.uk | www.thelimecentre.co.uk

Product Name: Earthborn Claypaint

- Earthborn claypaint is a solvent-free, long lasting paint for indoor walls and ceilings.
- It dries to a matt finish and is washable to DIN53778
- Good for covering and filling dry absorbent, grease-free surfaces such as wallpaper, wood, lime plaster and most common mineral surfaces as well as previously painted surfaces.
- Earthborn claypaint has exceptional breathability and absorbs variations in humidity which helps to destroy odours.
- Ideal for historic buildings and new build.
- It does not build up static and has proven beneficial to many asthma and allergy sufferers.

Coverage

Approx. 10m² per litre.

Vapour Permeability

SD value = 0.02m

Packaging

Keep containers sealed and store in a cool frost-free place.

Sample pots 100ml

2.5 Litres

5 Litres

Preparation

Loose particles of old paints should be removed with a brush or scraper. Sandy/powdery surfaces should first be stabilised with Earthborn Wall Glaze before applying clay paint. Stains which come through paint should first be treated with Earthborn Isolating Primer. Very smooth, non-absorbent surfaces must be sanded. Clay plaster must be moistened before application.

Application

Stir well before use. Apply paint with a roller or brush in a thin even coat. Spread the paint evenly in all directions. (You can also use a spray gun). On light-coloured smooth surfaces one coat is normally sufficient. On very absorbent surfaces such as fresh lime plaster use a priming coat of clay paint diluted with up to 20% water and finish with an undiluted final coat. Allow each coat to dry before the next is applied. Because Earthborn clay paint is a natural product there may be subtle variation in shade between batches; avoid starting a new container in the middle of a wall.

Drying Times

Earthborn claypaint can be painted over after 6-12 hours, depending on room temperature and relative humidity. The surface should be washable after 10 days.

Cleaning

It is important to clean rollers, brushes and tools using warm soapy water immediately after use. The term washable refers to the durability of the paint and its resistance to abrasion. It is often possible to remove surface marks using a pencil eraser or very fine emery paper, (test on a small area first).

Ingredients

Water, various clays, chalk, kaolin, vinegar ester, methylcellulose, various pigments, 0.1% synthetic preservatives.

The user is recommended to test the product on the intended surface to ensure its suitability